

Room

Harroldburg, Monroe Co. Indiana

Secr 11 & 14 T 10, R 18 18.

Nov. 17. 1886

K	I	L
Sec.	11	
C		
D		
E		
Sec.	14	G
H	F	
B	A	
M	L	

In accordance with accompanying
Notice published in
"Republican Progress"
Bloomington, Ind.
I made the following
Survey as per plat
and field notes accom-
panying, in sections
eleven and fourteen
Township 10 N. Range 18

NOTICE OF SURVEY.
NOTICE is hereby given to all non-
residents and all others interested,
that we will proceed together with the
County Surveyor of Monroe county, or
Deputy, on

TUESDAY, NOV. 28TH, 1886,
to run and establish all lines and corners
necessary to be established, in sections 14
and 11, town 10 range 1 east.
Meet at the center of said section 14 at
8 o'clock on said day.
You are requested to be present at said
time and place, else said survey will pro-
ceed in your absence.

DAVID S. DODSON,
JACOB FLEENER,
THOMAS LANDGUM,
Oct. 13, 1886.

James B. Fieke and John J. Shively
having been sworn in as chain-bearers
and Thomas Landrum as flagman I
began at "F" ran S. to "L", running 131 l. east and 45 l. N.,
corrected at point "A" establishing corner by planting a sand
stone witnessed by a 6 in hickory 8.35 & 38 l. and a 6 in hick-
ory 8.77 & 43 l. Then began at "L" ran S. ^{140 poles} coming out
69 l. N. and 15½ l. east of established corner at "A". I then
established a corner at "B" by planting a sandstone witnessed
by an 8 in black walnut ²⁷⁰ 8.48 l. and a 10 in wild
cherry 8.18½ W. 43½ l. I then at request of Mr. Hammond ran
and located the line BA finding it 110 l. longer than 80 poles.
I also, at request of David S. Dodson and Jacob Fleener
ran and located the line "FG". The above work was performed
on Tues and Wednes. On Wednes Lewis Neely acted as
sworn flagman. On Thurs. Nov. 11. with Jacob Fleener
as sworn flagman, and John J. Shively, and Mr. Jenkins
as "chain bearer" I began at "H" ran N. 320 poles. There
being no established corner at "I" I then began at "C" ran W. to
K. 160 poles and 47 l. came out 169 l. S. and 19 l. S. of "K"; then
corrected at "I"; found line from H to I to terminate 110 l. S.
and 6 l. W. of "I". I then proceeded to establish
at proportionate distances corners at C, D and E as follows
"C" a sand stone witnessed by ^{W. oak 24 in.} { 8.22 l.
"D" " " " { W. " 10 " N. 75 W. 65 l.
"E" " " " { Beech 12 " S. 16 E. 53 l.
" " " " { " 8 " 8.82 ^W 54 l.
" " " " { Red oak ^{4 ft.} " N. 47 W. 54 l.
" " " " { " 40 " 3.52 l.

I hereby certify the above to be a true
record of survey described during witness whereof I did, and seal Andrew Gillard Nov. 18.